

01-03-00

A



Docket No.: 99-1259

Patent Application

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of:

Kelly S. French

Entitled: **METHOD AND APPARATUS FOR COMMUNICATING STATE INFORMATION USING VERTICAL BLANKING INTERVAL**

December 30, 1999

To the Assistant Commissioner
for Patents
Box Patent Application
Washington, D.C. 20231

CERTIFICATE OF MAILING BY EXPRESS MAIL

"EXPRESS MAIL" Mailing Label No. EL 280 285 168 US

Date of Deposit December 30, 1999

I hereby certify that this paper or fee is being deposited with the U.S. Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and is addressed to the Assistant Commissioner for Patents, Washington, D.C. 20231

Penny L. Flint


Penny L. Flint
Signature

Dear Sir:

REQUEST FOR FILING A NATIONAL PATENT APPLICATION

Transmitted herewith for filing, please find the following:

- X 1. Specification, claims and abstract of the above-referenced patent application having 18 pages.
- X 2. 3 sheet(s) of drawing(s) (X formal / informal) comprising Figures 1 through 5 .
- X 3. Declaration and Power of Attorney (X signed unsigned).
- 3A. No filing fee, Oath, or Declaration is enclosed pursuant to 37 C.F.R 1.53(d).
- X 4. Information Disclosure Statement along with Form PTO-1449 and references.
5. This is a: Continuation-In-Part; Divisional; Continuation; substitute Application (MPEP 201.09) of Application Serial No. filed ; reissue of U.S. Patent No. filed on .



An extension to extend the life of the above prior Application to at least the date of filing hereof

(One box must be marked)

- (a) ☐ is concurrently being filed in that prior Application,
 (b) ☐ was previously filed in that prior Application,
 (c) ☐ is not necessary for copendency.

☒ 6. Attached is an assignment to **Spotware Technologies, Inc.** Please return the recorded assignment to the undersigned.

☐ 7. Priority is claimed under 35 U.S.C. § 119 based on filing in European Patent Office.

	<u>Application No.</u>	<u>Filing Date</u>
--	------------------------	--------------------

(1)	<input type="checkbox"/>	<input type="checkbox"/>
-----	--------------------------	--------------------------

(2)	<input type="checkbox"/>	<input type="checkbox"/>
-----	--------------------------	--------------------------

(3)	<input type="checkbox"/>	<input type="checkbox"/>
-----	--------------------------	--------------------------

☐ (No.) Certified copy (copies) ☐ are attached; or ☐ were previously filed on

☐ 8. Attached: ☐ (No.) verified statement(s) establishing "small entity" status under 37 CFR § 1.9 and 1.27.

☒ 9. Attached:

☒ Return Postcard
☐ (Other)

☐ 10. Preliminary Amendment:

Prior to a first Office Action, kindly amend the Application as follows:

11. The following Filing Fee calculation is based on the claims filed less any claims canceled by the Preliminary Amendment of Item 10.


					SMALL ENTITY RATE		LARGE ENTITY RATE		
BASIC FEE					\$380	<u>OR</u>	\$760	=	\$760.00
	NUMBER FILED			NUMBER EXTRA					
TOTAL CLAIMS	24	-20	=	4 (at least 0)	x 9	<u>OR</u>	x 18	=	+\$ 72.00
INDEP. CLAIMS	4	- 3	=	1 (at least 0)	x 39	<u>OR</u>	x 78	=	+\$ 78.00
If any <u>proper</u> multiple dependent claim (ignore improper) is present (Enter \$0.00 if this is a <u>reissue</u> application)					+\$130	<u>OR</u>	+\$260	=	+\$ 0.00
If assignment is x'd (item 6), add recording fee \$40.00									+\$ 40.00
Attached is a Rule 47 Petition (inventor refuses to sign or cannot be reached) \$130									+\$ 0.00
TOTAL FILING FEE									=\$950.00

12. A check in the amount of \$_____ to cover the Filing Fee calculated in Item 11 is attached. Please charge any deficiency or credit any overpayment to Deposit Account No. 50-0439.
- X 13. Please charge my Deposit Account No. 50-0439 in the amount of \$950.00 to cover the Filing Fee calculated in Item 11. This sheet is attached in duplicate.
- X 14. The Commissioner is hereby authorized to charge any fee specifically authorized hereafter, or any missing or insufficient fee(s) filed, or asserted to be filed, or which should have been filed herewith or concerning any paper filed hereafter, and may be required under 37 CFR 1.16-1.18 (missing or insufficiencies only) now or hereafter relative to this application and for the resulting Official Document under 37 CFR 1.20, and to have and cause any necessary petition for extension of time to be filed and any fees necessary to be paid for said extension of time OR credit any overpayment to our Deposit Account No. 50-0439, for which purpose a duplicate copy of this sheet is attached. **The Commissioner is not authorized to charge the issue fee until/unless an issue fee transmittal form is filed.**

DATED: December 30, 1999

Respectfully submitted,
Kelly S. French,

By:



Kenneth J. Cool
Reg. No. 40,570

Suiter & Associates PC
11516 Nicholas Street, Suite 205
Omaha, NE 68154-4409
Telephone: (402) 496-0300
Facsimile: (402) 496-0333

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

APPLICATION FOR PATENT

ON

METHOD AND APPARATUS FOR COMMUNICATING STATE INFORMATION
USING VERTICAL BLANKING INTERVAL

BY

KELLY S. FRENCH

METHOD AND APPARATUS FOR COMMUNICATING STATE INFORMATION USING VERTICAL BLANKING INTERVAL

5

FIELD OF THE INVENTION

The present invention generally relates to the field of information handling systems, and particularly to communicating information between an information handling system and a device coupled to the information handling system.

10

BACKGROUND OF THE INVENTION

The convergence of personal computer type information handling systems and television based information handling systems such as television tuners, videocassette recorders (VCRs), video laser disc player, digital versatile disk (DVD) players, and the like, have resulted in video information viewing systems with expanded features and capabilities and are often referred to as PC/TV's or convergence devices. In a typical convergence device, a personal computer core system is expanded to include hardware and software for coupling with and controlling standard video devices that provide standard video signals. For example, a convergence device may include a peripheral card that includes inputs for receiving the video and audio output provided by a VCR such that the video and audio signals may be processed and displayed or reproduced by the convergence device. The VCR, conforming with previously existing standards, receives infrared (IR) input commands from a control device capable of providing IR encoded input commands for controlling the VCR (e.g., record, play, stop, tune to specified television channels, etc.), for example a remote control device. The convergence device may include an infrared data encoder and transmitter for transmitting control commands from the convergence device to the VCR. However, more likely than not, the VCR is capable of receiving input commands and data only, and is not capable of returning information such as state data to the control device. The only outputs provided by a standard VCR are the video and audio signals. Thus, a device that is controlling a video device such as a VCR is not provided with data regarding the state or status of the video device, e.g.,

whether a received command was verified and successfully implemented, thereby making verification of control of the device difficult if not limited or impossible.

Encoding of information within a video signal has been implemented by previous systems. For example, Electronic Industry Association (EIA) standard EIA-608 defines a protocol for the transmission of data such as closed captioning information on field 2, line 21, of the vertical blanking interval (VBI) of a National Television Standards Committee (NTSC) video signal. Typically, an encoder at the broadcaster's location encodes closed captioning information into a video signal to be transmitted. A television receiver or VCR having a closed captioning decoder optionally decodes the encoded closed captioning data from the video signal and displays the data (i.e. text) on a portion of the television screen such that a subtitled text relating to words spoken in a program are available to hearing impaired viewers. Thus, the VBI encoding system is utilized to provide supplemental data in a broadcast television receiver. However, to date, no known system utilizes the vertical blanking interval to encode state information regarding a video device and to send the state information to a convergence device or PC/TV that controls the video device.

SUMMARY OF THE INVENTION

The present invention is directed to a system for communicating state information between a device and an information handling system that controls the device. In one embodiment, the system includes a signal processor for receiving a signal to be processed and an information handling system for receiving an output signal provided by the signal processor wherein the output signal is representative of at least a portion of the input signal. The information handling system provides a control signal to the signal processor and the signal processor encodes data onto the output signal in response to the control signal such that the encoded data is decodable by the information handling system. In another embodiment, the signal processor provides a video signal to the information handling system and the data is encoded in a vertical blanking interval of the video signal. The data may be indicative of the status of signal processor, including the status of execution of the command received by the information handling system. In one embodiment, the signal processing device is a VCR or similar device having an infrared control interface.

The present invention is further directed to a method for communicating state information between a device and an information handling system that controls the device. In one embodiment, the method includes steps for transmitting a control signal to a signal processor from an information handling system that controls the signal processor, receiving and decoding the control signal, providing an output signal from the signal processor to the information handling system, and encoding data onto the provided output signal in response to the control signal. The information handling system decodes the data from the output signal, and the data may be indicative of a the status of the signal processor, including a status of execution of the command signal. In one embodiment, the method is implemented on a signal processing device such as VCR or similar device having an infrared control interface. In a further embodiment, the method is implemented as a program of instructions storable on a computer readable medium for causing an information handling system to execute the steps of the method. In a particular embodiment, the method includes steps for encoding the data in an available vertical blanking interval of the output signal, and, in the event a vertical blanking interval is not available, interleaving the data in a previously existing data packet.

It is to be understood that both the forgoing general description and the following detailed description are exemplary and explanatory only and are not restrictive of the invention as claimed. The accompanying drawings, which are incorporated in and constitute a part of the specification, illustrate an embodiment of the invention and together with the general description, serve to explain the principles of the invention.

BRIEF DESCRIPTION OF THE DRAWING

The numerous advantages of the present invention may be better understood by those skilled in the art by reference to the accompanying figures in which:

FIG. 1 is a block diagram of an information handling system operable to tangibly embody the present invention;

FIG. 2 is a block diagram of a system for communicating between an information handling system and a device controlled by the information handling system in accordance with the present invention;

FIG. 3 is a block diagram of a preferred embodiment of a system for communicating state information in accordance with the present invention;

FIG. 4 is a block diagram of a communications system in accordance with the present invention; and

5 FIG. 5 is a flow diagram of a method for communicating state information in accordance with the present invention.

DETAILED DESCRIPTION OF THE INVENTION

Reference will now be made in detail to the presently preferred embodiment of
10 the invention, an example of which is illustrated in the accompanying drawings.

FIG. 1 shows a block diagram of an information handling system 100 in accordance with the present invention. In this embodiment, processor 102, system controller 112, cache 114, and data-path chip 118 are each coupled to host bus 110. Processor 102 is a microprocessor such as a 486-type chip, a Pentium®, Pentium II®,
15 Pentium III®, or the like suitable microprocessor. Cache 114 provides high-speed local-memory data (in one embodiment, for example, 512 KB of data) for processor 102, and is controlled by system controller 112, which loads cache 114 with data that is expected to be used soon after the data is placed in cache 112 (i.e. in the near future). Main memory 116 is coupled between system controller 112 and data-path
20 chip 118, and in one embodiment, provides random-access memory of between 16 MB and 128 MB of data. In one embodiment, main memory 116 is provided on SIMMs (Single In-line Memory Modules), while in another embodiment, main memory 116 is provided on DIMMs (Dual In-line Memory Modules), each of which plugs into suitable sockets provided on a motherboard holding these components and
25 many of the other components shown in FIG. 1. Main memory 116 includes standard DRAM (Dynamic Random-Access Memory), EDO (Extended Data Out) DRAM, SDRAM (Synchronous DRAM), or the like suitable memory technology. System controller 112 controls PCI (Peripheral Component Interconnect) bus 120, a local bus for system 100 that provides a high-speed data path between processor 102 and
30 various peripheral devices, such as video, disk, network, etc. Data-path chip 118 is also controlled by system controller 112 to assist in routing data between main memory 116, host bus 110, and PCI bus 120.

In one embodiment, PCI bus 120 provides a 32-bit-wide data path that runs at 33 MHz. In another embodiment, PCI bus 120 provides a 64-bit-wide data path that runs at 33 MHz. In yet other embodiments, PCI bus 120 provides 32-bit-wide or 64-bit-wide data paths that run at higher speeds. In one embodiment, PCI bus 120 provides connectivity to I/O bridge 122, graphics controller 127, and one or more PCI connectors 121, each of which accepts a standard PCI card. In one embodiment, I/O bridge 122 and graphics controller 127 are each integrated on the motherboard along with system controller 112, in order to avoid a board-to-connector-to-board signal crossing interface and thus provide better speed and reliability. In the embodiment shown, graphics controller 127 is coupled to a video memory 128 that includes memory such as DRAM, EDO DRAM, SDRAM, or VRAM (Video Random-Access Memory), and drives VGA (Video Graphics Adapter) port 129. VGA port 129 can connect to VGA-type or SVGA (Super VGA)-type displays or the like. Other input/output (I/O) cards having a PCI interface can be plugged into PCI connectors 121.

In one embodiment, I/O bridge 122 is a chip that provides connection and control to one or more independent IDE connectors 124-125, to a USB (Universal Serial Bus) port 126, and to ISA (Industry Standard Architecture) bus 130. In this embodiment, IDE connector 124 provides connectivity for up to two or more standard IDE-type devices such as hard disk drives, CD-ROM (Compact Disk-Read-Only Memory) drives, DVD (Digital Video Disk or Digital Versatile Disk) drives, or TBU (Tape-Backup Unit) devices. In one similar embodiment, two IDE connectors 124 are provided, and each provide the EIDE (Enhanced IDE) architecture. In the embodiment shown, SCSI (Small Computer System Interface) connector 125 provides connectivity for preferably up to seven or fifteen SCSI-type devices (depending on the version of SCSI supported by the embodiment). In one embodiment, I/O bridge 122 provides ISA bus 130 having one or more ISA connectors 131 (in one embodiment, three connectors are provided). In one embodiment, ISA bus 130 is coupled to I/O controller 152, which in turn provides connections to two serial ports 154 and 155, parallel port 156, and FDD (Floppy-Disk Drive) connector 157. In one embodiment, FDD connector 157 is connected to FDD 158 that receives removable media (floppy diskette) 159 on which is stored data and/or program code 160. In one such

embodiment, program code 160 includes code that controls programmable system 100 to perform the method described below. In another such embodiment, serial port 154 is connectable to a computer network such as the internet, and such network has program code 160 that controls programmable system 100 to perform the method
5 described below. In one embodiment, ISA bus 130 is connected to buffer 132, which is connected to X bus 140, which provides connections to real-time clock 142, keyboard/mouse controller 144 and keyboard BIOS ROM (Basic Input/Output System Read-Only Memory) 145, and to system BIOS ROM 146.

FIG. 1 shows one exemplary embodiment of the present invention, however
10 other bus structures and memory arrangements are specifically contemplated. In one embodiment, I/O bridge 122 is a chip that provides connection and control to one or more independent IDE connectors 124-125, to a USB (Universal Serial Bus) port 126, and to ISA (Industry Standard Architecture) bus 130. In this embodiment, IDE connector 124 provides connectivity for up to two standard IDE-type devices such as
15 hard disk drives or CD-ROM (Compact Disk-Read-Only Memory) drives, and similarly IDE connector 125 provides connectivity for up to two IDE-type devices. In one such embodiment, IDE connectors 124 and 125 each provide the EIDE (Enhanced IDE) architecture. In one embodiment, I/O bridge 122 provides ISA bus 130 having one or more ISA connectors 131 (in one embodiment, three connectors are
20 provided). In one embodiment, ISA bus 130 is coupled to I/O controller 152, which in turn provides connections to two serial ports 154 and 155, parallel port 156, and FDD (Floppy-Disk Drive) connector 157. In one embodiment, ISA bus 130 is connected to buffer 132, which is connected to X bus 140, which provides connections to real-time clock 142, keyboard/mouse controller 144 and keyboard
25 BIOS ROM (Basic Input/Output System Read-Only Memory) 145, and to system BIOS ROM 146. It should be appreciated that modification or reconfiguration of information handling system 100 of FIG. 1 by one having ordinary skill in the art would not depart from the scope or the spirit of the present invention.

Referring now to FIG. 2, a block diagram of a system for communicating
30 between an information handling system and a device controlled by the information handling system will be discussed. Information handling system 100 is utilized to interface with a device such as a VCR 210 such that information handling system 100

is capable of controlling VCR 210. Information handling system 100 provides control and command signals to VCR 210 via a communications link 214. Communications link 214 is preferably a wireless link that provides for the transfer of information via a wireless medium. For example, communications link 214 is an infrared (IR) communications link that transmits IR encoded information from information handling system 100 to VCR 210 in accordance with well-known IR transmission standards such as an Infrared Developers Association (IrDA) standard. Alternatively, wireless link 214 is a radio-frequency (RF) communications link that transmits RF modulated information from information handling system 100 to VCR 210 using well-known RF modulation and transmission techniques. For a typical VCR, communications link 214 is a unidirectional link such that information is capable of flowing from information handling system 100 to VCR via communications link 214, but not in the reverse direction. VCR 210 provides an output that couples with information handling system 100 via a video optimized transmission line 216, such as a 75 ohm coaxial cable, RCA type cable, S-video cable, fiber optic cable, etc. Typically, the output provided by VCR is a video signal, and may include a separate audio signal or signals (e.g., via mono RCA audio output or stereo RCA audio outputs), or the audio and video signals may be combined into a single signal via a single output such as is the case with a 75 ohm coaxial cable type output. Normally, the flow of information via transmission line 216 is also unidirectional wherein information flows from VCR 210 to information handling system 100. The output signal provided by VCR 210 on transmission line 216 is a video signal reproduced from an information storage medium (e.g., a videocassette), or may be a pass-through of an input signal 212 received by VCR 210 with little or no processing being performed on input signal (except perhaps buffering, impedance matching, etc.), or with some signal processing being performed on input signal 212 before being provided as an output signal on transmission line 216 (e.g., tuning, color and contrast processing, etc.). In accordance with the present invention, information handling system 100 controls VCR 210 by providing a control signal to VCR via communications link 214, for example, turn on/off, start recording input signal 212, stop recording input signal 212, play back information stored on an information storage medium, fast forward, rewind, tune to a specific channel contained in input

signal 212, program recording of a specific channel at a predetermined time, etc. In response to a control signal received from information handling system 100, VCR executes the requested task accordingly. The status of VCR 210 (e.g., recording, paused, playing back video, tuning to a channel, etc.) and related data (e.g., present track time/location, the number of the channel tuned to, etc.) is provided back to information handling system 100 via transmission line 216 so that the state information and data (i.e. status data) does not interfere with the output signal also transmitted via transmission line 216. In the case where the output signal is a video signal, status data is encoded into a vertical blanking interval (VBI) of the video signal. The feeding back of status information to information handling system 100 allows for the monitoring of implementation of control commands and further allows a user to be informed of status information.

Referring now to FIG. 3, a block diagram of a preferred embodiment of a system for communicating state information in accordance with the present invention will be discussed. Information handling system 100 includes an IR transmitter 310 for transmitting an IR encoded control signal to VCR via IR communications link 214. VCR 210 includes an IR receiver for receiving the IR encoded control signal, an IR decoder 314 for decoding the IR encoded signal, and a controller 316 for receiving the decoded control signal and then executing the control signal appropriately. Controller 316 is also utilized for controlling the functions and operation of VCR 210 such as programming, recording, playing, etc. VCR 210 includes a recording medium system 322 for recording information onto an information storage medium (e.g., magnetic videocassette tape), and for playing back information stored on an information storage medium (e.g., movies, television programs, etc.) that is provided to a video output circuit 320 for providing the played back information as an output signal on transmission line 216. Input signal 212 is provided to a video input circuit 324 that provides input signal to recording medium system 322 and video output circuit 320. A VBI decoder 326 decodes information previously encoded in input signal 212, for example, closed captioning information.

Upon receiving a control signal from information handling system 100, controller 316 provides data such as status information to VBI encoder and inserter 318 that encodes the data in a vertical blanking interval of the output signal provided

by video output circuit 320. Data may also be encoded onto the output signal periodically such that the data may be periodically updated. Also, status information may be provided when the status information has changed, for example, playback counter information may be continuously provided as data encoded in a VBI of the output signal. Thus, VCR 210 may provide status information continuously, at
5 predetermined intervals, when requested by information handling system 100, or in response to a received control signal, etc. Information handling system 100 receives the output signal provided by VCR 210 with a video input circuit 328 disposed in information handling system 100. A VBI decoder 330 decodes the data from the
10 output signal such that the data may be interpreted by information handling system 100. The decoded data is then available to be processed if required (e.g., by processor 102) or provided to a user (e.g., provided to VGA port 129 for display on a display coupled to information handling system 100). The received output signal is capable of being processed, if required, stored on an information storage medium
15 (e.g., medium 159), provided to VGA port 129 for reproduction on a display coupled to information handling system 100, etc. The system as shown and described with respect to FIG. 3 thereby allows information such as status data to be communicated from VCR 210 to information handling system 100 to provide monitoring and control of VCR 210 with information handling system. In a preferred embodiment, the
20 output signal provided by VCR 210 conforms with an NTSC standard, and data is encoded onto the output signal in conformance with an Electronic Industry Association (EIA) standard. For example, data is encoded according to EIA standard EIA-608 "Recommended Practice for Line 21 Data Service" that defines a protocol for the transmission of data on field 2, line 21 of the Vertical Blanking Interval (VBI)
25 of an NTSC signal such as described with respect to the Extended Data Services (EDS) of parts 1.6, 5.6, 6 and 10 of EIA-608. In such an embodiment, using a specific EDS packet class and sub-packet format would allow the encoding device to store and send state information along with the signal as discussed herein. The packet class to be used may be the "Miscellaneous" class (07h-03h character pair) to identify
30 the packet as one that holds a Supplemental Data Location (EIA-608 parts 6.5.4) that indicates on which line of the VBI the data is disposed. At the location specified, data is encoded by VBI encoder/insertor 310 for receipt by VBI decoder 330. Each packet

is capable of containing different types of data using the first byte of the pair to identify the contents of the current packet with the remaining bytes containing data. The format of the data is not required to be in compliance with any particular standard, however a standard packet format and VBI location may be optimally
5 utilized to provide compatibility between hardware devices (such as VCR 210) from differing manufacturers. VBI decoder 330 reads data packets that utilize the Supplemental Data Location to detect the existence of data packets encoded in other lines of the VBI. In such an embodiment, VBI encoder/insertor 318 can dynamically select in which line of the VBI to encode the data. In the event all lines are in use, a
10 new data packet may be interleaved with a previously existing data packet such as described in EIA-608 part 5.6.

Referring now to FIG. 4, a block diagram of a communications system in accordance with the present invention will be discussed. The communications system shown in FIG. 4 is substantially similar to the communication system shown in and
15 discussed with respect to FIG. 2 wherein VCR may be any device or signal processor 410 coupled with and controlled by information handling system 100 in a manner similar to VCR 210. For example, signal processor 410 may be a video laser disc player, a digital versatile disk (DVD) player, a Moving Pictures Expert Group (MPEG) compliant video player, or any other similar audio, video or multimedia
20 player or the like. Thus, signal processor 410 receives a control signal from information handling system 100 whereby information handling system is capable of controlling signal processor 410. Signal processor receives an input signal 412 and provides an output signal to information handling system 100 via transmission line 416. Data such as status information may be encoded onto the output signal by signal
25 processor 410 such as in a VBI in the case where the output signal is a video signal. Information handling system 100 decodes the data from the output signal whereby the data may be interpreted accordingly such that state information may be communicated from signal processor 410 to information handling system 100.

Referring now to FIG. 5, a flow diagram of a method for communicating state
30 information in accordance with the present invention will be discussed. Method 500 may be implemented as a program of instructions executed by processor 102 of information handling system 100 and/or controller 316 of VCR 210 or signal

processor 410, alone or in combination, that is storable on an information storage medium, such as medium 159, readable by an information handling system or similar computer system. A control signal is transmitted at step 510 from information handling system 100 and received by VCR 210 or signal processor 410 at step 512.

5 The control signal is decoded at step 514, and a control command represented by the control signal is executed at step 516 as appropriate. An output signal is provided at step 518 by VCR 210 or signal processor 410. A determination is made at step 520 whether there is an available VBI in the output signal in which to encode a packet of data. In the event there is no available VBI, a new data packet is interleaved with a

10 previously existing data packet at step 522. Data is then encoded into a VBI at step 524. The encoded data may be, for example, representative of a status of VCR 210 or signal processor 410 or the status of execution of the command encoded in the control signal. The output signal is received by information handling system 100 at step 526 which then scans the output signal at step 528 for a VBI having an encoded data

15 packet. When a VBI having an encoded data packet is located, the data is decoded from the output signal at step 530 such that the data may be interpreted and acted upon as appropriate, including providing the status information to a user. The output signal is reproduced at step 532 by information handling system.

Although the invention has been described with a certain degree of particularity, it should be recognized that elements thereof may be altered by persons skilled in the art without departing from the spirit and scope of the invention. One of the embodiments of the invention can be implemented as sets of instructions resident in the main memory 116 of one or more computer information handling systems configured generally as described in FIG. 1. Until required by the computer system,

20 the set of instructions may be stored in another computer readable memory such as information storage medium 159 of FIG. 1, for example in a hard disk drive or in a removable memory such as an optical disk for utilization in a CD-ROM drive, a floppy disk for utilization in a floppy disk drive, a floptical disk for utilization in a floptical drive, or a personal computer memory card for utilization in a personal

25 computer card slot. Further, the set of instructions can be stored in the memory of another computer and transmitted over a local area network or a wide area network, such as the Internet, when desired by the user. Additionally, the instructions may be

30

transmitted over a network in the form of an applet (a program executed from within another application) or a servlet (an applet executed by a server) that is interpreted or compiled after transmission to the computer system rather than prior to transmission. One skilled in the art would appreciate that the physical storage of the sets of
5 instructions, applets or servlets physically changes the medium upon which it is stored electrically, magnetically, chemically, physically, optically or holographically so that the medium carries computer readable information.

It is believed that the method and apparatus for communicating state information using vertical blanking interval of the present invention and many of its
10 attendant advantages will be understood by the foregoing description, and it will be apparent that various changes may be made in the form, construction and arrangement of the components thereof without departing from the scope and spirit of the invention or without sacrificing all of its material advantages, the form herein before described being merely an explanatory embodiment thereof. It is the intention of the following
15 claims to encompass and include such changes.

CLAIMS

What is claimed is:

1. A system, comprising:
a signal processor for receiving a signal to be processed; and
an information handling system for receiving an output signal provided by said signal processor, the output signal being representative of at least a portion of the input signal, wherein said information handling system provides a control signal to said signal processor and said signal processor encodes data onto the output signal in response to the control signal such that the encoded data is decodable by said information handling system.
2. A system as claimed in claim 1, said signal processor including a data encoder for encoding the data onto the output signal, and said information handling system having a data decoder for decoding the data from the output signal received from said signal processor.
3. A system as claimed in claim 1, said information handling system having a transmitter for transmitting the control signal to said signal processor, and said signal processor having a receiver and decoder for receiving and decoding the control signal received from said information handling system.
4. A system as claimed in claim 1, said information handling system being capable of reproducing the output signal received from said signal processor.
5. A system as claimed in claim 1, the signal to be processed and the output signal provided by said signal processor being video signals.
6. A system as claimed in claim 1, the output signal provided by said signal processor being a video signal, the data being encoded into a vertical blanking interval of the output signal.

7. A system as claimed in claim 1, the output signal provided by said signal processor being an NTSC compliant video signal, the data being encoded onto a vertical blanking interval of the NTSC compliant video signal.

8. A system as claimed in claim 1, the output signal provided by said signal processor being an NTSC compliant video signal, the data being encoded onto a vertical blanking interval of the NTSC compliant video signal in compliance with an Electronic Industry Association standard.

9. A system as claimed in claim 1, the control signal being a wireless signal.

10. A system as claimed in claim 1, said signal processor being an information storage media player.

11. A system, comprising:
means for processing a received signal;
means for transmitting a control signal to said processing means;
means, coupled with said processing means for receiving and decoding
the control signal;
means, coupled with said processing means, for encoding data onto an
output signal provided by said processing means in response to the control signal; and
means for transmitting the output signal to said transmitting means
wherein said transmitting means is capable of decoding the encoded data from the
provided signal.

12. A system as claimed in claim 11, the data being indicative of a status
of execution of the control signal.

13. A system as claimed in claim 11, the data being indicative of a status
of said processing means.

14. A system as claimed in claim 11, said processing means including
means for storing at least a portion of the received signal to an information storage
medium and for reproducing at least a portion of the stored signal as the output signal.

~~15.~~ A method, comprising:
transmitting a control signal to a signal processor from an information handling system that controls the signal processor;
receiving and decoding the control signal;
providing an output signal from the signal processor to the information handling system; and
encoding data onto the provided output signal in response to the control signal.

16. A method as claimed in claim 15, the provided output signal being a video signal, said encoding step including encoding the data in a vertical blanking interval of the video signal.

17. A method as claimed in claim 15, further comprising the step of decoding the data from the provided output signal.

18. A method as claimed in claim 15, the data being indicative of a status of the signal processor.

19. A method as claimed in claim 15, further comprising the steps of encoding the data in an available vertical blanking interval of the output signal, and, in the event a vertical blanking interval is not available, interleaving the data in a previously existing data packet.

20. A program of instructions storable on a computer readable medium for causing an information handling system to execute a series of steps, the steps comprising:

transmitting a control signal from an information handling system to a signal processor that the information handling system controls;

receiving and decoding the control signal;

providing an output signal from the signal processor to the information handling system; and

encoding data onto the output signal in response to the control signal.

21. A program of instructions as claimed in claim 20, the steps further including the step of decoding the data from the output signal.

22. A program of instructions as claimed in claim 20, the data being indicative of a state of the signal processor.

23. A program of instructions as claimed in claim 20, the output signal being a video signal wherein the data is encoded into a vertical blanking interval of the video signal.

24. A program of instructions as claimed in claim 20, the steps further comprising the steps of encoding the data in an available vertical blanking interval of the output signal, and, in the event a vertical blanking interval is not available, interleaving the data in a previously existing data packet.

METHOD AND APPARATUS FOR COMMUNICATING STATE INFORMATION
USING VERTICAL BLANKING INTERVAL

5

ABSTRACT

An information handling system controls a signal processing device by providing a control signal to the signal processing device. The control signal may be transmitted to the signal processing device as an infrared or R/F signal that is received and decoded by the signal processing device. The signal processing device is capable of receiving and processing an input signal, and is further capable of providing an output signal to the information handling system. In response to the control signal, the signal processing device encodes data onto the output signal provided to the information handling system, and the information handling system is capable of decoding the data from the output signal. The data encoded onto the output signal may include status information from the signal processing device, including the status of execution of the control signal. In one embodiment, the output signal is a video signal, such as the case where the signal processor is a VCR or the like, and the data is encoded onto a vertical blanking interval of the video signal such that state information is communicated from the signal processor to the information handling system via the vertical blanking interval.




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5

DECLARATION

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled Method and Apparatus for Communicating State Information Using Vertical Blanking Interval

the specification of which

(Check One): X is attached hereto.
 was filed on _____ as

Application Serial No. _____

and was amended on (if applicable) _____

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment(s) referred to above. I acknowledge the duty to disclose information which is material to the patentability of this application in accordance with Title 37, Code of Federal Regulations, § 1.56 printed on the reverse side of this Declaration. I hereby claim foreign priority benefits under Title 35, United States Code §119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed.

Application No.	Country	Date of Filing	Priority Claimed	
			Yes	No
None				

I hereby claim the benefit under Title 35, United States Code, § 120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, § 112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, § 1.56 which occurred between the filing date of the prior application and the national or PCT international filing date of this application.

Application No.	Date of Filing	Status-Patented, Pending or Abandoned
None		

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

SIGNATURE(S)

Full name of **first inventor** Kelly S. French

Inventor's signature Kelly French

Date 12/16/99 Country of Citizenship USA

Residence Hurst, TX

Post Office Address 628 Redbud Drive, Hurst, TX 76053

Full name of **second joint inventor**

Inventor's signature _____

Date _____ Country of Citizenship _____

Residence _____

Post Office Address _____

Full name of **third joint inventor**

Inventor's signature _____

Date _____ Country of Citizenship _____

Residence _____


Post Office Address _____

POWER OF ATTORNEYSPOTWARE TECHNOLOGIES, INC., Assignee(s) of the application for United States Letters Patent forMethod and Apparatus for Communicating State Information Using Vertical Blanking Interval
(Title)by Kelly S. French
(Inventors)X executed on the date(s) as indicated on the corresponding Declaration and Assignment therein, or
— having Serial No. _____, filed _____.

a copy of the Assignment of which is attached hereto, do(es) hereby appoint as attorneys of record with full power of substitution and revocation, to prosecute this application and transact all business in the Patent and Trademark Office connected therewith:

Mark S. Walker, Reg. No. 30,669
Anthony Claiborne, Reg. No. 39,636
Joseph H. Lee, Reg. No. 37,664
Sean P. Suiter, Reg. No. 34,260
Scott C. Rand, Reg. No. 40,359
Kenneth J. Cool, Reg. No. 40,570
Kevin E. West, Reg. No. 43,983
William J. Breen, III, Reg. No. 45,313Address correspondence to: **Suiter & Associates, PC**
Attention: **Kenneth J. Cool**
11516 Nicholas Street, Suite 205
Omaha, NE 68154-4409
Telephone: (402) 496-0300
Facsimile: (402) 496-0333

I, the undersigned, declare that I am empowered to execute this Power of Attorney on behalf of the Assignee. The above-identified Assignee is the owner of this application by reason of an assignment being filed with the Patent Office for recordation concurrently herewith. In accordance with 37 CFR § 3.373(b), I certify that I have reviewed all documents in the chain of title, and to the best of my knowledge, all right, title, and interest is in the above-identified Assignee, and I further declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further, that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application or any patent issuing thereon.

Full Name of Assignee	SPOTWARE TECHNOLOGIES, INC.	
Post Office Address	4545 Towne Centre Court, San Diego, CA 92121-3030	
Signature of Declarant or Assignee		Date 12-22-99

Full Name of Declarant If Other Than Assignee	Mark S. Walker, Reg. No. 30,669
Title of Declarant	Assistant Secretary
Address of Declarant	4545 Towne Centre Court, San Diego, CA 92121-3030